


# ERGONOMIC CUSTOMISED WORKING ENVIRONMENT



## LIFT SOLUTIONS CAN BE FOUND AT EDMOLIFT

EdmoLift offer a new and comprehensive tilt program with a range of tilt combinations.

Assembly of the tilt unit can be mounted on the lift table platform or directly on the floor. For installation on the platform the hydraulics are the same for the tilting device and table. Tilting devices installed directly on the floor have a base frame and integral power pack.

The tilt function is used to incline the lift table and make the goods more accessible in more ergonomically designed work places. Examples of work places are control functions for loading and off loading of goods as well as production work places. The load carrier can be a pallet, crate or container. The tilt can be customised to suit individual needs and wishes of the customer.

At EdmoLift you can find solutions for all your lifting problems.

## PRODUCT FEATURES

- ◆ Single-operation hydraulics 45° tilt angle.
- ◆ Double-operation hydraulics 90° tilt angle.
- ◆ Torque 6.5 KNm and 13 KNm.
- ◆ Platform length 900 mm, 1300 mm, 1700 mm.
- ◆ Platform width 600 mm, 800 mm, 1000 mm.
- ◆ Slide protection 230 mm include.
- ◆ Complies with European safety standard EN 1570-1 – CE certified.
- ◆ 24 V DC control unit and operating device with deadman's switch.
- ◆ IP54 approved electrical system.
- ◆ Safety spacing between all moving parts.
- ◆ Overload protection.
- ◆ Adjustable trap prevention safety trip bars on all four sides of the platform.
- ◆ Maintenance-free bearing surface.
- ◆ PLC control for simple customizing to specific requirements.
- ◆ User manual in 20 different languages.



## PRODUCT INFORMATION

Model	Art.no	Length mm	Width mm	Closed height mm	Tilt angle	Hydraulic	Tilt over	Torque kNm	kW	Weight incl. pack. kg	Execution
EDLF 65	36085	1300	800	320	90°	Double acting	800	6,5	0,75	165	Floor installation
ESLF 65	36076	800	1300	320	45°	Single acting	1300	6,5	0,75	165	Floor installation

### CE- or Type 2B declaration

We construct and manufacture our lift tables and lift trolleys in accordance with the basic requirements in the Lift table standards EN 1570-1 and the Lift trolley standards SS-EN ISO 3691-5:2009. We comply with the requirements in accordance with Machine, Low voltage and the EMC directive. The products are delivered after being tested with CE certification and the assurance of agreement or in certain cases the manufacturer's Type 2B declaration.

